

SecurPhone SIP

Weatherproof (IP65) and vandal resistant (IK09)
SIP security telephones



IP65 weatherproof protection

- Superior resistance to dust and water
- Perfect for inside or outside installation

IK09 vandal-resistant

- 4mm thick aluminium housing - Tamper resistant proof screws
- Vandal-resistant buttons and keypad
- Armed handset cord which cannot be dismantled

Efficient

- Flush or surface mount
- Keypad with Braille dots
- Keypad, buttons and label display can be continuously back-lighted and (or) when going off-hook and (or) when ringing
- Flashing leds can be activated when going off-hook and (or) when ringing
- Adjustable amplified speaker
- 2 auxiliary dry contacts to activate cameras, lights, etc. when going off-hook and (or) when ringing
- Adjustable ringer volume (6 steps) up to 100dB
- Hearing aid compatible
- EEPROM memory backup

SIP

- 1 SIP account (SIP v2 compatible)
- PoE powered or with external power supply (included)
- Auto-provisionning - Automatic firmware update
- Web interface configuration
- DHCP - PPPoE - @IP fixe client
- Second failover server (DNS - Proxy)
- Network Address Translation (NAT) - SNTP
- Get @IP by voice menu
- Audio codecs: G.711, G.723, G.726, G.729
- QoS - VAD - CNG - LEC - Packet Loss Compensation
- Administrator / User password - TLS - SRTP



SecurPhone SIP

Weatherproof (IP65) and vandal resistant (IK09)
SIP security telephones



5 models

- No keypad / Hot line call (automatic dialling of one programmed number) when picking up the handset
- No keypad 2 memory buttons
- No keypad 4 memory buttons
- Keypad
- Keypad and 4 memory buttons

Description	No keypad models	Models with keypad
Number of buttons	0 - 2 or 4	0 or 4
PoE or with power supply (included)	•	•
Keypad, buttons and label display backlight activation	•	•
Flashing leds activation (off-hook, ringing)	•	•
Keypad with Braille dots	•	•
EEPROM memory backup	•	•
Hearing aid compatible	•	•

Technical specifications	No keypad models	Models with keypad
Flush or surface mount	•	•
Vandal-resistant with IK09 rating	•	•
IP65 weather resistance	•	•
Natural ventilation	•	•
2 auxiliary dry contacts	•	•
Amplified speaker	•	•
Adjustable ringer volume (6 steps) up to 100dB	•	•
Dimensions (mm) flush mount	290 x 120 x 56	290 x 120 x 56
Dimensions (mm) surface mount	294 x 125 x 59	294 x 125 x 59
Red color (optional)	•	•



HENRI DEPAEPE S.A.S.

75/77 rue du Pré Brochet | 95110 SANNOIS - France
Tél.: +33 (0) 1 30 25 81 60 | Fax: +33 (0) 1 39 98 61 24

www.depaepe.com | © Copyright HENRI DEPAEPE SAS 2019. Reproduction interdite. Photos non contractuelles.

DEPAEPE Télécommunications se réserve le droit de modifier sans préavis les caractéristiques de ses produits en vue d'y apporter des améliorations techniques ou de respecter de nouvelles réglementations, nationales ou internationales

